

LOS ANGELES COUNTY
SOLID WASTE MANAGEMENT COMMITTEE/
INTEGRATED WASTE MANAGEMENT TASK FORCE
900 SOUTH FREMONT AVENUE, ALHAMBRA, CALIFORNIA 91802-1460
P.O. BOX 1460, ALHAMBRA, CALIFORNIA 91802-1460
www.lacountyiswmtf.org

MARK PESTRELLA – CHAIR MARGARET CLARK– VICE CHAIR

February 5, 2018

Ms. Nicole Stetson Waste Management 1200 W. City Ranch Road Palmdale, CA 93551

Dear Ms. Stetson:

FINDING OF CONFORMANCE REQUIREMENTS
ANTELOPE VALLEY LANDFILL
1200 W. CITY RANCH ROAD, PALMDALE, CA.
SOLID WASTE FACILITY PERMIT NO. 19-AA-5624

The Los Angeles County Solid Waste Management Committee/Integrated Waste Management Task Force (Task Force) has been advised that Waste Management, Antelope Valley Recycling & Disposal Facility, Inc., has submitted an application for a revised Solid Waste Facility Permit (SWFP) for the subject facility with the Local Enforcement Agency. Amongst other things, the revision to the SWFP entailed increasing the permitted facilities maximum daily tonnage from 3,564 to 5,548 tons per day (tpd), and updating the estimated closure year from 2042 to 2032.

Pursuant to the Los Angeles County Countywide Siting Element (CSE), new solid waste disposal facilities, expansions of existing solid waste disposal facilities, or existing solid waste disposal facilities that institute a significant change to their operation (such as a permit revision) must obtain a Finding of Conformance (FOC) with the CSE from the Task Force. The CSE was approved by a majority of cities in the County containing a majority of the cities' population, the County Board of Supervisors, and the former California Integrated Waste Management Board on June 24, 1998. The purpose of the FOC is to ensure that any new and/or expansions of solid waste disposal facilities in Los Angeles County, including the cities and unincorporated communities, are consistent with the CSE and its siting criteria.

To apply for an FOC, please submit the required minimum information according to the enclosed Table 10-1. To demonstrate compliance with the siting criteria established in Chapter 6 of the Countywide Siting Element, please fill out the attached Siting Criteria

Ms. Stetson February 5, 2018 Page 2

form. A complete copy of "Countywide Siting Element Vol. I" can be downloaded by visiting <a href="www.LACountySWIMS.org">www.LACountySWIMS.org</a> or at the following direct link: <a href="http://dpw.lacounty.gov/epd/swims/ShowDoc.aspx?id=115&hp=yes&type=PDF">http://dpw.lacounty.gov/epd/swims/ShowDoc.aspx?id=115&hp=yes&type=PDF</a>.

Pursuant to Chapter 3.67 of the Los Angeles County Code and the California Integrated Waste Management Act of 1989 (AB 939, as amended), the Task Force is responsible for coordinating the development of all major solid waste planning documents prepared for the County of Los Angeles and the 88 cities in Los Angeles County with a combined population in excess of 10 million. Consistent with these responsibilities, and to ensure a coordinated and cost-effective and environmentally sound solid waste management system in Los Angeles County, the Task Force also addresses issues impacting the system on a countywide basis. The Task Force membership includes representatives from the League of California Cities-Los Angeles County Division, County of Los Angeles Board of Supervisors, City of Los Angeles, the waste management industry, environmental groups, the public, and a number of other governmental agencies.

If you have any questions, please contact Martin Aiyetiwa, staff to the Task Force at (626) 458-3553, Monday through Thursday, from 7 a.m. to 5 p.m.

Sincerely,

Margaret Clark

Margaret Clark, Vice Chair Los Angeles County Solid Waste Management Committee/ Integrated Waste Management Task Force and Council Member, City of Rosemead

SS:mg

P:\eppub\EnvAff\EA\TF\TF\Letters\2018\January\Antelope Valley Landfill Application for an FOC

cc: County of Los Angeles Department of Public Health (Maurice Pantoja, Dorcas Hanson-Lugo, Janet Chairez Gallardo)

City of Palmdale, Planning Manager (Rob Bruce)

Each Member of the Los Angeles County Integrated Waste Management Task Force Each Member of the Facility and Plan Review Subcommittee

Facility Name: Location:

SITING FACTORS	GENERAL CRITERIA	CRITERIA MET		EXPLANATION FOR MEETING OR
		YES	NO	NOT MEETING CRITEIRA
A. PROTECT THE RESIDENTS				
· Proximity to populations	Facility must be in conformance with local land use and zoning requirements of a county or city planning agency.			
	Construction of buildings or structures on or within 1,000 feet of a land disposal facility must contain a natural or manmade protective system.			
B. ENSURE THE STRUCTURAL	STABILITY AND SAFETY OF THE FACIL	.ITY		
- Flood hazard areas	Disposal facilities must comply with requirements of the Federal Clean Water Act, as amended and local Stormwater/Urban Runoff requirements.			
	Land Disposal Facilities must be designed, constructed, operated, and maintained to prevent inundation or washout due to floods with a 100-year return period.			
<ul> <li>Areas subject to tsunamis, seiches, and storm surges.</li> </ul>	Disposal facilities should avoid areas subject to such events unless designed, constructed, operated, and maintained to preclude failure due to such events.			
Proximity to active or potentially active faults/seismic				

	New or expansion of Class III landfill is prohibited on a known		
	Holocene Fault.		
· Slope stability	Facilities should have engineered design safety features to assure structural stability.		
- Subsidence/liquefaction	All facilities should avoid locating in areas subject to such change unless designed, constructed, and maintained to preclude failure as a result of such change.		
Dam failure inundation areas	Facilities should be located outside dam failure inundation areas.		
C. PROTECT SURFACE WATER		•	
· Aqueducts and reservoirs	New and existing Class III landfills should be fitted with subsurface barriers, as well as, precipitation and drainage control facilities.		
<ul> <li>Discharge of treated effluent</li> </ul>	Facilities should be located in areas with adequate sewer capacity to accommodate the expected wastewater discharge. On site treatment should be considered if no sewers are available.		
	Facilities discharging into streams or into the ocean, directly or via storm drains, will require National Pollutant Discharge Elimination System Permits issued by the Regional Water Quality Control Board.		

D. PROTECT GROUNDWATER				
Proximity to supply wells and well fields	Facilities must meet State of California's geologic setting criteria for ensuring no impairment of beneficial uses of surface water or of groundwater beneath or adjacent to the landfill.			
· Depth to groundwater	All containment structures must be capable of withstanding hydraulic pressure gradients to prevent failure due to settlement, compression, or uplift.			
	Class III landfills should be fitted with containment structures that meet specified Federal and State permeability standards. Facility to be fitted with groundwater collection system and leachate collection and removal systems.			
- Groundwater monitoring reliability	Facilities must comply with the California RWQCB permit requirements for groundwater monitoring.			
· Major aquifer recharge areas	Facilities must meet State of California's minimum requirements for ensuring no impairment of beneficial use of surface water or groundwater beneath or adjacent to landfill.			
<ul> <li>Permeability of surficial materials</li> </ul>	Class III landfills should be underlain by a composite liner, consisting of lower clay liner and upper synthetic membrane, and which is of sufficient thickness to prevent vertical movement of fluids including waste and leachate.			

<ul> <li>Existing groundwater quality</li> </ul>	Facility should meet California Water Quality Control Board's minimum water quality protection standards and criteria.		
E. PROTECT AIR QUALITY			
<ul> <li>Prevention of significant deterioration (PSD) areas</li> </ul>	Facilities located in regions which are classified under PSD regulation as major stationary sources will be required to submit to preconstruction review and apply the Best Available Control Technology.		
· Non-attainment areas	Facilities with air emissions located in non-attainment areas and emitting air contaminants in excess of established limits will require preconstruction review under New Source Review requirements and the obtaining of a Permit to Construct and a Permit to Operate from the Antelope Valley Air Quality Management District.		
· Landfill surface emissions	Class III land disposal facilities are subject to AVAQMD rules and regulations which includes installation of a landfill gas control system and perimeter monitoring probes, as well as, implementation of a monitoring program to ensure that landfill gas emissions do not exceed specified AVAQMD standards.		

F. PROTECTION OF ENVIRONMENTALLY SENSITIVE AREAS				
· Wetlands	Land disposal facilities should be located outside wetlands areas.			
<ul> <li>Proximity to habitats of threatened and endangered species</li> </ul>	A facility should not locate in habitats of threatened or endangered species unless the local land use authority makes a determination that a proposed facility is compatible with the surrounding resources and does not pose a substantial threat to the resource.			
- Agricultural lands	A facility located in areas zoned for agricultural uses must obtain a local land use permit from the local jurisdiction.			
<ul> <li>Natural, recreational, cultural, and aesthetic resources</li> </ul>	Facilities should avoid locating in these areas unless the applicant can demonstrate that a facility is compatible with the land use in the area.			
· Significant ecological areas	Location of a proposed facility must be in conformance with local jurisdiction's General Plan and abide by Federal and State regulations regarding unique or protected species and their habitat.			
G. ENSURE SAFE TRANSPORTATION OF SOLID WASTE				
<ul> <li>Proximity to areas of waste generation</li> </ul>	Facilities should be centrally located near wasteshed areas to minimize potential impacts associated with greater travel distances.			
	Alternate transportation, by rail, may be evaluated in regard to specific sites to be located at distant areas from the wasteshed.			

Distance from major route	Distance traveled on minor roads should be kept to a minimum.				
Structures and properties fronting minor routes	Facilities should be located such that any minor routes from the major route to the facility are used by trucks, and the number of nonindustrial structures is minimal.				
. Highway accident rate	The minimum time path from major wasteshed areas to a facility should follow highways with low to moderate average annual daily traffic and accident rates.				
Capacity vs. average Annual     Daily Traffic (AADT) of     access roads	The changes in the ratio capacity to AADT should be negligible after calculating the number of trucks on the major and minor routes expected to service the facility.				
H. PROTECT THE SOCIAL AND	H. PROTECT THE SOCIAL AND ECONOMIC DEVELOPMENT GOALS OF THE COMMUNITY				
· Consistency with General Plan	The proposed facility must be consistent with the County or City General Plan. Also, it must be in conformance with the Countywide Siting Element of the County of Los Angeles, by obtaining FOC granted by Los Angeles County Solid Waste Management Committee/Integrated Waste Management Task Force.				

# Table 10-1 Finding of Conformance Submittal Requirements

Proponents of solid waste disposal (landfill and transformation) facilities, except otherwise exempted, must submit proposals to the Los Angeles County Solid Waste Management Committee/Integrated Waste Management Task Force for an FOC. The facility proposal shall contain the following minimum information:

- I. Identity of project proponent, owner, and operator.
- 2. Description of project location.
- 3. Project implementation schedule (as applicable) including planned dates for construction start, construction completion, start-up, planned expansion. and closure.
- 4. Project design capacity or acreage as appropriate.
- 5. Description of waste material to be handled.
- 6. Identification of waste sources.
- 7. Projection of waste quantity to be handled at start-up and at five-year intervals in project's life.
- 8. Identification of waste transport corridors and destination.
- 9. Technology to be used for treatment facilities.
- I0. Planned site classification for disposal sites.
- II. Planned end uses for the land for disposal sites.
- 12. Final environmental documentation (initial study, negative declaration, categorical exemption, or an Environmental Impact Report) including all Notices of Determinations showing the posting dates »:ith the County Clerk/City Clerk and the State Office of Planning and Research.
- 13. Planned market for materials/energy recovered from resource recovery projects.
- 14. Description of proposed waste diversion/salvage programs to be operated at the facility.
- 15. Information and operations plan for meeting applicable permit/regulatory requirements.
- 16. Demonstration of compliance with siting criteria requirements as established in Chapter 6 of the CSE.
- 17. Demonstration of compliance with general plan consistency requirements as required by the California Public Resources Code, Section 50000.5 and 5000 I, as applicable. In addition, a copy of the appropriate land use permit shall also be provided.
- 18. A tarping program designed to prevent the accidental release of litter from vehicles entering and leaving the site.
- 19. A waste load-checking program designed to prevent disposal of hazardous and other unacceptable waste from the site.

### Table 10-1 (continued)

A set of plans, drawn-to-scale, clearly identifying property lines, adjacent land uses, all structures such as scale house, administration buildings, locations of any above ground or underground storage tanks, surrounding streets and access roads, etc. The plans must be a minimum of2 feet by 3 feet in dimension, clearly labeled and bearing the signature and seal of a California Registered Civil Engineer. For land disposal facilities, the plans must show initial and final grades for and delineate the extent of the fill area. For transformation facilities, the plans must show drainage and wastewater discharge lines, the incineration building and equipment, and materials recovery area (if any).

In addition, the facility owner/operator will be required to implement the following measures/programs:

- I. Project proponents of new Class III landfills and owners/operators of expansions of existing Class III landfills shall be required to implement the following seismic monitoring requirements:
  - a) Install an accelerometer on site to measure seismic ground motions by a date to be established by the Task Force. A set of as-built plans signed and sealed by a California Registered Civil Engineer shall be provided to the Local Enforcement Agency and the Los Angeles County Department of Public Works, Environmental Programs Division for approval.
  - b) Following a major seismic event: I) of magnitude 5.0 or greater in the Ritcher Scale, as recorded by the closest ground-motion monitoring device as maintained by the California Division of Mines and Geology, and 2) with an epicenter located within 25 miles from the Landfill (or as directed by the Task Force), thoroughly survey the landfill site for primary and secondary surface expressions of seismic activity (such as, surface ruptures, landslides, changes in spring flows, liquefaction, etc.). Submit a damage assessment report on the results of the survey to the Los Angeles County Department of Public Works, Environmental Programs Division and the Local Enforcement Agency for review. The assessment report must describe and discuss all features, including damage to the site and infrastructure caused by the seismic event, and the measures that will be taken to mitigate the impact.
- ..., All Class III landfill owners/operators shall be required to submit a description of the program that will be implemented at the facility to:
  - a) Minimize disposal of inert waste at their facility.
  - b) Maximize density of disposed materials.
  - c) Use green waste or other appropriate materials for use as landfill daily cover other than soil, subject to approval of the appropriate Local Enforcement Agency, the CIWMB, and other appropriate permitting agencies.
- 3. All solid waste disposal facility operators shall be required to submit a description of the program that will be implemented at the facility to:
  - a) Acquire and provide to the County all data necessary for cities in Los Angeles County and the County to comply with the mandates of Assembly BiU 939. Additionally, disposal facility operators will be encouraged to institute waste salvage operations in compliance with all applicable rules and regulations.
  - b) Discourage transportation of uncovered waste to the disposal facility through vehicle tarping enforcement at the gate.
  - c) Control litter on the streets, highways, and properties surrounding the disposal facility.